



## XE0-S1P0-LX

### 100 Mbps managed PCI bus fiber NIC

XE0-S1P0-LX 100 Mbps managed PCI bus fiber NIC

Product Information	
<b>Model number:</b>	XE0-S1P0-LX
<b>Description:</b>	100 Mbps PCI SC Connector Fast Ethernet Fiber NIC
<b>Size/pc:</b>	120 mm x 53 mm
<b>Color:</b>	As picture
<b>Features:</b>	<p>Based on Taiwan VIA VT6105M controller            100 M 1*9 module, MM or SM available            Both full-height and low profile for small form factors            Support PXE Boot ROM            Compliant with IEEE 802.3u 100Base-FX/IEEE 802.3ah 100Base-LX10/-BX10 ethernet standards            100 Mbps fast ethernet, full duplex or half-duplex, reach 200 Mbps in full duplex            Supports 32-bit PCI 2.2 buses            Support IEEE 802.3x Flow Control enabled with full duplex operation, allowing enhanced operation when directly connected to a switch            Support IP Unicast broadcast and multicast address filtering mechanism            IEEE 802.1p Tagging supported, ensure the sensitive data can reach on time            Support IEEE 802.1Q VLAN tagging            Support GVRP VLAN registration protocol            Support TCP/IP, CPU Task Offload reduces host CPU use            Advanced management, support DMI 2.0 and ACPI 1.0            Wavelength 1310 nm</p>
<b>Specification:</b>	<p>NOS Software Support:            Microsoft Windows 2000/2003/XP/Vista/Win7 (32 or 64 bit)            Microsoft NT 3.51/4.0            Microsoft Windows for Workgroups 3.11            Microsoft Windows CE.NET 4.0/4.2            Microsoft Client for DOS            Linux 5.15, 5.20            Novell Netware Client for DOS            Novell Netware Client 32 for DOS            Novell Netware Server 3.12, 3.2, 4.11, 4.2, 5.0, 5.1            ODI for DOS driver            32 bit ODI LAN driver            SCO Open Server 5.0.x</p> <p>Environmental Parameters:            Operating Temperature: 0 --50 C            Storage Temperature: 5--55 C            Humidity Range Operating: 5% --95%, non-condensing            Power: 2 W            LED: green Link/Activity, orange and green color indicated            Size: 120 mm x 53 mm</p>