



# LB9A

## 1 G/10 G Enterprise-class Ethernet Switch



### Overview

The Xenopt LB9A is a high performance layer 2/3/4 Ethernet switch with 48 10Base-T/100Base-TX/1000Base-T ports and 4 dual speed 1 GbE/10 GbE SFP+ ports in a compact rack unit size.

### Simplicity

The Xenopt LB9A can be managed through industry-standard command-line Interface (CLI) which reduces the training and operating costs. A user friendly Web GUI is provided via a standard Web browser to manage. The LB9A also supports Simple Network Management Protocol (SNMP) both from standard MIB and private MIB for network administrator to easily configure, monitor, and manage remotely. The Auto-Installation feature implemented in the Xenopt LB9A helps centralized management to simplify deployment of a truly plug-and-play experience. With the evolution from IPv4 to IPv6, The LB9A is a IPv6 integrated management device.

### High Availability

The Xenopt LB9A is designed for high availability from both hardware and software perspective. The key features include:

- Out-of-band management supported
- 802.1D, 802.1w, and 802.1s supported
- Up to 8 ports per link aggregation group (LACP) and up to 64 groups
- Multi-chassis LAG for preventing the risks of single point failure
- Up to 32 paths ECMP routing for load balancing and redundancy
- Virtual Router Redundancy Protocol supported

### High-Performance L2/L3 access deployments

- With the compact 1U form factor, high density 48 gigabit ports and 4 dual speed 1GbE/10GbE uplink ports, the Xenopt LB9A is ideal for enterprise campus application.
- The 176Gbps switching capacity and 131Mpps forwarding rate ensures high bandwidth connectivity to the aggregation or core layers and low power consumption ensure LB9A to be a powerful solution to aggregate data traffic and high-performance servers.
- The 4-port 10GbE density in a 1U height switch provides near 1:1 subscription ratio throughout the network. This brings the benefits to organizations to deploy highly utilized networks and avoid congestion during peak hours.

### Advanced IPv4 and IPv6 routing

The Xenopt LB9A is a fully layer 2 and layer 3 routing switch that supports advanced IPv4 and IPv6 routing features such as RIP v1/v2, OSPF, ECMP, RIPng and OSPFv3. The multicast routing features for IGMP v1/v2/v3, DVMRP, PIM-DM/SM, MLD v1/v2 and PIM-DM6/SM6 are all supported in the LB9A.

### Features

#### Performance

- 48 10Base-T/100Base-TX/1000Base-T with 4 1/10GbE dual speed SFP+ ports in 1 RU
- 176 gigabit per second
- 131 million packets per second
- 12K jumbo frame

#### Layer 2 features

- 4093 configurable VLANs
- Multi-chassis Link Aggregation

#### Security

- L2/L3/L4 security
- Storm control

#### Management

- Industrial command-line interface
- Dual images
- Web-based GUI (HTTP/HTTPS)
- sFlow
- IPv6 management
- Auto-Installation

#### Layer 3 features

- RIP v1/v2
- OSPF
- ECMP
- IGMP v1/v2/v3
- PIM-DM/SM
- Policy-based Routing

#### IPv6 support

- RIPng
- OSPFv3
- MLD v1/v2
- PIM-DM6/SM6

## Networking LB9A specifications

### Physical ports

- 48 10Base-T/100Base-TX/1000Base-T ports
- 4 1GbE/10GbE dual speed SFP+ ports
- 1 RJ-45 out-of-band management port (10/100/1000)
- 1 RJ-45 console port

### Performance

- Switching capacity: 176Gbps
- Forwarding rate: 131Mpps
- Memory: 1024MB DDR1
- Flash: 64MB
- MAC: 32K
- Packet buffer: 4MB
- Jumbo frame: 12K

### L2 features

- Auto-negotiation for port speed and duplex
- Flow control: IEEE 802.3x / back-pressure
- Switching mode: store-and-forward
- Spanning Tree Protocol:
  - 802.1D, 802.1w, and 802.1s
  - Spanning Tree Fast Forwarding
  - Edge port, Loop guard
  - BPDU filter/guard
  - Auto Edge
  - TCN guard, Root guard
- VLANs
  - IEEE 802.1Q tagged based
  - Port-based (up to 4093 user configurable VLANs)
  - GVRP/GMRP
  - 802.1v protocol VLAN
  - Voice VLAN
  - MAC-based VLAN
  - IP-subnet VLAN
  - QinQ
- VTP v1/v2
- Private VLAN
- Storm control
  - Broadcast
  - Unknown multicast
  - Unknown unicast
- IGMP snooping
  - IGMP snooping v1/v2/v3
  - IGMP v1/v2 querier
  - IGMP immediate leave
- Link Aggregation
  - 802.3ad with LACP
  - Cisco EtherChannel Like
  - Unicast/Multicast traffic balance over trunking port (dst-ip, dst-mac, src-dst-ip, src-dst-mac, src-ip, src-mac)
- Multi-chassis Link Aggregation (MLAG)
- Link state, Port backup

### QoS

- Queues per port: 8 queues
- QoS queue management using Weighted Round Robin (WRR), Strict Priority (SP) and hybrid (WRR+SP)
- COS: 802.1p, IP Precedence, and DSCP
- DiffServ, Port rate limit
- Auto VoIP
- iSCSI optimization

### Security

- Static and dynamic port security (MAC-based)
- 802.1x: port-based, MAC-based, auto VLAN assignment, guest VLAN, unauthenticated VLAN
- ACL: L2/L3/L4
- IPv6 ACL: L3/L4
- RADIUS: authentication and accounting (up to 32servers)
- TACACS+: authentication (up to 5 servers)
- HTTPS (AES 128-cbc, 3ES-cbc, Blowfish-cbc)
- SSH v1.5/v2.0 (AES 128-cbc, 3ES-cbc, Blowfish-cbc)
- User name and password: local authentication and remote authentication via RADIUS/TACACS+
- Denial of Service control
- Management IP filtering (SNMP/Web/Telnet/SSH)
- MAC filtering
- IP Source Guard
- Dynamic ARP inspection (DAI)
- DHCP snooping

### Management

- Industrial command-line interface
- CLI filtering
- Telnet/SSH
- HTTP/HTTPS
- Software download/upload: TFTP/Xmodem/FTP
- Configuration download/upload: TFTP/Xmodem/FTP
- Dual image backup supported
- SNMP v1/v2c/v3
- RMON 1, 2, 3 and 9
- BOOTP: client/relay
- DHCP: client/relay/option 82
- Event/error log: local flash and remote server via system log (RFC3164)
- DNS: client/relay
- SNMPv4
- LLDP (802.1ab, Link Layer – Discovery Protocol)
- CDP (Cisco Discovery Protocol) version 2
- Port mirroring: one to one and many to one
- sFlow v5
- Auto-Installation
- IPv6 management:
  - IPv4/IPv6 Dual Stack
  - ICMPv6
  - ICMPv6 redirect
  - IPv6 Path MTU Discovery
  - IPv6 Neighbor Discovery
  - stateless auto-configuration
  - manual configuration
  - DHCPv6 (client)
  - SNMP/HTTP/SSH/Telnet over IPv6
  - IPv6 DNS resolver
  - IPv6 RADIUS/TACACS+ support
  - IPv6 Syslog support
  - IPv6 SNMP, IPv6 TFTP
  - IPv6 Ping

### Layer 3 features

- IP Multinetting/CIDR
- /31 subnets
- ARP (static: 128 and dynamic – 3968)
- Proxy ARP, Local proxy ARP
- IRDP, Static route
- Unicast Routing: RIP v1/v2, SPF
- ECMP
- Multicast Routing: IGMP 1/v2/v3, DVMRP, PIM-DM/-SM
- IGMP proxy
- Source IP Configuration
- Policy-based routing
- VRRP

### IPv6 Layer 3 features

- Static route
- Unicast Routing: RIPng and OSPFv3
- Multicast Routing: MLD v1/v2, PIM-DM6/-SM6

### Mechanical

- Dimension (HxWxD): 42.4x440x283.6 mm
- Weight: 3.9kg (NET)

### Environmental specifications

- Operating temperature: 0~45°C
- Operating humidity: 90% maximum relative humidity

### Safety

- UL 60950-1 (2nd Ed.)
- CSA C22.2 60950-1-07 (2nd Ed.)
- IEC 60950-1 (2nd Ed.)
- EN 60950-1 (2009)
- CNS 14336-1, GB4943.1-2011

### EMC

- FCC 47CFR, Part 15 Subpart B Class A
- ICES-003 Class A
- EN 55022-2010 Class A
- EN 55022-2010
- CISPR 22: 2008 Class A
- CISPR 24: 2010
- EN 61000-3-2:2006/A1: 2009/A2: 2009
- IEC 61000-3-2:2005/A1: 2008/A2: 2009
- EN 61000-3-3: 2008
- IEC 61000-3-3: 2008
- EN 300 386 v1.5.1:2010
- VCCI V-3/2012.04 Class A
- JEITA IT-3001: 2004
- KCC KN 22, KN 24
- BSMI EMC CNS 13438 95
- CCC EMC GB9254-2008

### Environmental

- Reduction of Hazardous Substances (RoHS) 6

### Order information

- LB9A

### Warranty

- Limited lifetime warranty

**Ordering information<sup>1</sup>**

PN	Description
<b>Switches</b>	
X1LB9BZZ0ST2	Switch, 1U, 48G+4x10G SFP+, (standard L2/L3 FW), dual PSU, Air Flow Direction Front to Back
<b>Cables 10 G</b>	
XCD-SFSFNgg	Cable, 10GbE, Direct attach, Copper, SFP+ to SFP+, length: gg = {01 - 1m; 02 - 2m; 03 - 3m; 04 - 4m; 05 - 5m}
XCE-SFSFNgg	Cable, 10GbE, Direct attach, Optic, SFP+ to SFP+, length: gg = {01 - 1m; 02 - 2m; 03 - 3m; 04 - 4m; 05 - 5m; 06 - 6m; 07 - 7m; 10 - 10m; 20 - 20m; 50 - 50m; C1 - 100m}
<b>Pluggables</b>	
XSM311-02LY	SFP, multimode, 1310nm, 1Gbps, 2km, LC, with DDMI (0 ± 70OC)
XSM851-M5LY	SFP, multimode, 850nm, 1Gbps, 500m, LC, with DDMI (0 ± 70OC)
XSSdd1-ffLh	SFP, singlemode, dd = {31 - 1310nm; 55 - 1550nm}, 1Gbps, ff = {20 - 20km; 40 - 40km; 80 - 80km; C0 - 120km; G0 - 160km; I0 - 180km; K0 - 200km}, LC, h = {N - no DDMI; Y - DDMI (0 ± 70OC)}
XSBdd1-ffgh	SFP, bidirectional, dd = {27 - 1270nm; 29 - 1290nm; ... ; 61 - 1610nm}, 1Gbps, ff = {20 - 20km; 40 - 40km; 80 - 80km; C0 - 120km}, g = {L - LC, S - SC}, h = {N - no DDMI; Y - DDMI (0 ± 70OC)}
XSCdd1-ffLh	SFP, CWDM, 1Gbps, dd = {lower WL: 27 - 1270nm; ... 45 - 1450nm / upper WL: 47 - 1470nm; ... ; 61 - 1610nm}, ff = {40 - 40km; 80 - 80km; C0 - 120km; G0 - 160km; I0 - 180km; K0 - 200km}, LC, h = {N - no DDMI; Y - DDMI (0 ± 70OC)}
XSDdd1-ffLY	SFP, DWDM C-BAND, dd = {17 - 61 ITU grid channel}, 1Gbps, ff = {80 - 80km; C0 - 120km}, LC, with DDMI (0 ± 70OC)
XTM85A-M3LY	SFP+, multimode, 850nm, 10Gbps, 300m (OM3), LC, with DDMI (0 ± 70OC)
XTS31A-ffLY	SFP+, singlemode, 1310nm, 10Gbps, ff = {02 - 2km; 10 - 10km; 20 - 20km; 40 - 40km}, LC, with DDMI (0 ± 70OC)
XTS55A-ffLY	SFP+, singlemode, 1550nm, 10Gbps, ff = {40 - 40km; 80 - 80km; A0 - 100km}, LC, with DDMI (0 ± 70OC)
XTBddA-ffLY	SFP+, bidirectional, dd = {27 - 1270nm; 32 - 1330nm; }, 10Gbps, ff = {10 - 10km; 20 - 20km; 40 - 40km; 60 - 60km}, LC, with DDMI (0 ± 70OC)
XTCddA-ffLY	SFP+, CWDM, dd = {27 - 1270nm; 29 - 1290nm; ... ; 61 - 1610nm}, 10Gbps, ff = {10 - 10km; 40 - 40km; 80 - 70/80km}, LC, with DDMI (0 ± 70OC)
XTDddA-ffLY	SFP+, DWDM C-BAND, dd = {17 - 61 ITU grid channel}, 10Gbps, ff = {40 - 40km; 80 - 80km*}, LC, with DDMI (0 ± 70OC)
XTDTCA-ffLY	SFP+, DWDM C-BAND, Tunable, 10Gbps, ff = {40 - 40km; 80 - 80km}, LC, with DDMI (0 ± 70OC)
XTLTLA-ffLY	SFP+, DWDM L-BAND, Tunable, 10Gbps, ff = {40 - 40km; 80 - 80km}, LC, with DDMI (0 ± 70OC)
<b>Services</b>	Services
<b>Spare PS Unit</b>	Spare Power Supply Unit
<b>SW&amp;FW</b>	Firmware and software

**Notes:**

<sup>1</sup> For accurate order specification please contact Xenopt reseller before placing an order. The content of this document is subject to change without notice. Xenopt does not guarantee errorless or outdated information.

**Important Notice**

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by XenOpt before they become applicable to any particular order or contract. In accordance with the XenOpt policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of XenOpt or others. Further details are available from any XenOpt sales representative.

To find out more, please contact: